

Model 102 T-K CLASS 125 GATE VALVE

NON RISING STEM, NPT

(30 SERIES)

Job Name:	Contractor:	
Job Location:	P.O. Number: Representative:	
Engineer:		
Tag:	Wholesale Distributor:	

Description

The Apollo Model 102T-K Gate Valve provides a cost effective "made in the USA" alternative to globally sourced multi-turn valves. These valves are cast, machined, assembled, and tested in South Carolina. The Apollo Gate Valve can reliably be installed in most plumbing and heating systems (or building service piping).

Features

- Full Port
- · Guided Solid Bronze Disc
- · Adjustable Graphite Stem Packing
- Non-Rising Stem
- Dezincification Resistant
- All Bronze Construction
- 100% Factory tested
- NPT Connection
- · Screw-in Bonnet
- Rugged Bronze "Cross" Handle
- 100% machined and assembled in USA
- · Back seat protection

Standards

• ASME B1.20.1, "Pipe Threads, General Purpose (Inch)"

Performance Rating

Saturated Steam: 125 psi (8.6 Bar) to 353°F(178°C) Cold Working Pressure: 200 psi (13.8 Bar) at 100°F

Temperature Range: -20°F to 406°F

Order Information

Size	Model	Item Number Thread (NPT)	
1/2"	102TK	30-033-01K	
3/4"	102TK	30-034-01K	
□ 1"	102TK	30-035-01K	
□1-1/4"	102TK	30-036-01K	
1-½"	102TK	30-037-01K	
□ 2"	102TK	30-038-01K	
2-1/2 "	102TK	30-039-01K	
□ 3"	102TK	30-030-01K	







Material Specifications

Part Name	Material Material	
Body	ASTM B62 Bronze	
Bonnet	ASTM B62 Bronze	
Stem	ASTM B371 Bronze	
Disc	ASTM B62 Bronze	
Packing	Grafoil®	
Packing Nut	ASTM B16 Brass	
Handle	ASTM B584 Bronze	

Dimensions

Size	Height (open) In.	Length (in.)	Weight (Lbs)	Cv (gpm)
1/4"	3.29	1.76	.74	3.0
3/8"	3.29	1.76	.71	6.0
1/2"	3.56	2.03	.85	12.5
3/4"	4.05	2.07	1.19	24.0
1"	4.55	2.45	1.98	72.3
1-1/4"	5.14	2.63	2.8	80.0
1-1/2"	6.02	2.88	3.95	119.0
2"	7.09	3.06	5.88	338.0
2-1/2"	9.11	4.13	12.19	395.0
3"	12.61	4.48	16.84	435.0

Conbraco Industries, Inc. 701 Matthews Mint Hill Rd. Matthews NC 28105 USA; www.apollovalves.com; 704-841-6000